## HX 70/...-IC-F61

# Helical Antenna for ICOM Portable Equipment in the 70 cm Band $\,$

### DESCRIPTION

- Short conical steel helix moulded in flexible thermoplastic rubber.
- Reduced-size ¼ λ helical antenna whip.
- Optimum performance compared to physical dimensions.
- Delivered factory tuned and tested to ensure minimum SWR.
- Especially designed for ICOM IC-F61 (450 MHz band).




### ORDERING DESIGNATIONS

TYPE	PRODUCT NO.	FREQUENCY
HX 70/s-IC-F61	140000199	380 – 410 MHz
HX 70/I-IC-F61	140000202	400 – 430 MHz
HX 70/m-IC-F61	140000327	420 – 450 MHz
HX 70/h-IC-F61	140000200	440 – 470 MHz

### **SPECIFICATIONS**

ELECTRICAL	
MODEL	HX 70/IC-F61
ANTENNA TYPE	Shortened ¼ λ helical antenna for portable equipment
FREQUENCY	70 cm band covered by four models
IMPEDANCE	Nom. 50 Ω
POLARISATION	Vertical
GAIN	Approx3 dB (compared to a $\frac{1}{4}$ $\lambda$ portable antenna on the same equipment)
BANDWIDTH	≥ 20 MHz @ SWR ≤ 2.0
SWR	<1.5 when mounted directly on portable equipment
MAX. POWER	50 W
MECHANICAL	
MATERIALS	Steel helix moulded in flexible thermoplastic rubber Weather- and shockproof plastics Black-chromed brass
COLOUR	Black
TOTAL HEIGHT	Approx. 65 mm (dep. on type)
WEIGHT	Approx. 20 g
CONNECTOR	1/4"-32 UNEF

### TYPICAL SWR CURVE





PROCOM France S.A.R.L. se réserve le droit d'améliorer les spécifications sans préavis.

