
MU 2401/UMTS-MMS

0 dB Mobile Antenna for the UMTS Band (1900 – 2200 MHz)

DESCRIPTION

- Mobile antenna for the UMTS Band (1900 2200 MHz).
- Black-chromed whip in nice, discrete design.
- Approx. 0 dB gain.
- MMS-mount professional quality in elegant and smooth design.
- Low profile magnetic mount.
- Provided with FME-connection (supplied without cable).



Ordering designations

| TYPE NO. | PRODUCT NO. |
|------------------|-------------|
| MU 2401/UMTS-MMS | 130001276 |

SPECIFICATIONS

| ELECTRICAL | |
|----------------|---|
| MODEL | MU 2401/UMTS-MMS |
| ANTENNA TYPE | 1/4 λ mobile antenna |
| FREQUENCY | UMTS band (1900 – 2200 MHz) |
| IMPEDANCE | Nom. 50 Ω |
| POLARISATION | Vertical |
| GAIN | Approx. 0 dB (acc. to EIA RS-329-1) |
| BAND WIDTH | ≥ 200 MHz @ SWR ≤ 2 |
| SWR | ≤ 1.75 @ f. res. |
| MAX. POWER | 25 W |
| MECHANICAL | |
| MATERIALS | Whip: Black-chromed brass Mount: Black-chromed brass and steel Silicone layer on contact surface All materials are chosen to avoidcorrosion |
| CABLE | FME-cable to be ordered separately |
| COLOUR | Black |
| HEIGHT | Approx. 60 mm |
| WEIGHT | Approx. 250 g |
| MOUNTING | Centre of vehicle roof for best omnidrectionalcoverage |
| MAX. CAR SPEED | 180 km/h |


INSTALLATION


The MU 2401/UMTS-MMS should be mounted at the centre of the vehicle roof to ensure best omnidirectional coverage.

The MMS-mount is especially suited for temporary antenna installations where it is not desirable to drill a hole in the vehicle. The magnetic mount can advantageously serve several vehicles by shifting it from one vehicle to another. The MMS-mount is provided with a thoroughly magnetized permanent ring magnet positioned in a carefully shaped magnetic circuit which yields an extraordinarily high attaching effect and makes this mount stand for very high values of bending moment and mechanical shock.

A silicone layer applied to the contact surface protects the car roof and ensures maximum friction.

INSTALLATION DIMENSIONS





2. TUNING

The antenna is delivered factory-tuned and requires no further tuning.

PLEASE NOTE

For safety reasons: When using the MU 2401/UMTS-MMS car speed must not exceed $180 \ \text{km/h}.$



PROCOM France S.A.R.L. se réserve le droit d'améliorer les spécifications sans préavis. 15/12/11

